REFERENCES

[1] FCC. (2002, Nov). Spectrum Policy Task Force report, Tech. Rep. 02-135. [Online]. Available at http://www.hraunfoss.fcc.gov/edocs_public/attachmatch/DOC-228542A1.pdf.

[2] J. Mitola (2000), “Cognitive radio: An integrated agent architecture for software defined radio.” Ph.D. Dissertation, KTH, 2000.

[3] D. Cabric, S. Mishra, D. Willkomm, R. Brodersen, and A. Wolisz(2005), "A Cognitive Radio Approach for Usage of Virtual Unlicensed Spectrum”, ISTA Mobile Wireless Communications Summit, June 2005.

[4] S. Haykin(2005), “Cognitive radio: Brain-empowered wireless communications,” IEEE Journal on Selected Areas in Communications, Vol. 23, No. 2,Feb. 2005,pp. 201–220, DOI 10.1109/JSAC.2004.839380.

[5] Paul J. Kolodzy(2005), “Coginitive Radio Fundamentals”, SDR Forum, Singapore, April 2005.

[6] Linda E Doyle(2009), ”Essentials of Cognitive Radio”, Cambridge University Press, First Edition, United Kingdom.

[7] Kwang-Cheng Chen, and Ramjee Prasad(2009),”Cognitive Radio Networks”, Wiley Publications, First Edition, United Kingdom.

[8] EkramHossain, DusitNiyato, and Zhu Han(2009),”Dynamic Spectrum Access and Management in Cognitive Radio Networks”, Cambridge University Press, United Kingdom.

[9] R. W. Thomas, L. A. DaSilva, and A. B. MacKenzie(2005), “Cognitive Networks”, in Proc.First IEEE International Symposium onNew Frontiers in Dynamic Spectrum Access Networks, DySPAN’05,Baltimore, MD, USA,Nov. 2005, pp. 352-360, DOI 10.1109/DYSPAN.2005.1542652.

[10] HuseyinArslan(2007), “Cognitive Radio, Software Defined Radio, and Adaptive Wireless Systems”, Springer Publications, Netherlands, First Edition 2007.

[11] Anthony Ephremides and Bruce Hajek(1998), ” Information Theory and Communication Networks: An Unconsummated Union”,IEEE transactions on Information Theory, vol. 44, no. 6, Oct. 1998, pp. 2416-2434, DOI 10.1109/18.720543.

[12] Andrea Goldsmith, Sayed Ali Jafa, IvanaMaric and SudhirSrinivasa(2009), “ Breaking Spectrum Gridlock with Cognitive Radios: An Information Theoretic Perspective”, in Proc. of IEEE Journal in May 2009, Volume 97, issue 5, pp. 894-914, DOI 10.1109/JPROC.2009.2015717.

[13] Ian F. Akyildiz, Won-Yeol Lee, Mehmet C. Vuran, ShantidevMohanty(2006), “NeXt generation/dynamic spectrum access/cognitive radio wireless networks:A survey”, Computer Networks, Vol. 50, No. 13, Sept.2006, pp. 2127-2159, available online at www.sciencedirect.com.

[14] Syed Ali Jafar, and SudhirSrinivasa(2007), *“*Capacity Limits of Cognitive Radio With Distributed and Dynamic Spectral Activity*”*, IEEE journal on selected areas in communications, Vol. 25, No. 3, Apr. 2007, pp. 529-537, DOI 10.1109/JSAC.2007.070403.

[15] SudhirSrinivasa and Sayed Ali Jafar (2006), “The Throughput Potential of Cognitive Radio: A Theoretical Perspective”, in Proc. of Fortieth Asilomar Conference on Signals, Systems and Computers, ACSSC '06,Nov. 2006, pp. 221-225, DOI 10.1109/ACSSC.2006.356619.

[16] Marco AjmoneMarsan and Daniele Roffinella (1983),“Multichannel Local Area Network Protocols”, IEEEjournal on selected areas in communications, vol. SAC-1, no. *5,* Nov.1983, pp. 885-897, DOI 10.1109/JSAC.1983.1145994.

[17] IEEE Standard (1997),“Wireless LAN mediumaccess control (MAC) and physical layer (PHY) specification”, in IEEE standard 802.11-1997.

[18] D. Raychaudhuri and Xiangpeng Jing(2003), “ASpectrum Etiquette Protocol for Efficient Coordination of Radio Devices in Unlicensed Bands”, in Proc. of 14th IEEE International Symposium on Personal, Indoor and Mobile Radio Communication,Vol. 1, pp. 172-176, Sept.2003, DOI 10.1109/PIMRC.2003.1264255.

[19] J. So and N Vaidya(2004), “Multi-channel MAC for Ad Hoc Networks: Handling Multi-Channel Hidden Terminals using a Single Transceiver”, MobiHoc’ 04, Roppongi Japan, pp. 222-233, DOI 10.1145/989459.989487.

[20] A. Raniwala, K. Gopalan, T. Chiueh(2004), “Centralized Channel Assignment and Routing Algorithms for Multi-Channel Wireless Mesh Networks”,ACM SIGMOBILE Mobile Computing and Communications Review(MC2R), vol. 8, no. 2, pp. 50–65, April 2004, DOI 10.1145/997122.997130.

[21] AsisNasipuri, Jun Zhuang, and Samir R. Das (1999),“A Multichannel CSMA MAC Protocol for Multihop Wireless Networks”,in Proc. of IEEE Wireless Communications and Networking Conference, WCNC ‘99, New Orleans, LA, Sep. 1999, Vol. 3, pp. 1402-1406, DOI 10.1109/WCNC.1999.796968.

[22] AsisNasipuri and Samir R. Das(2000), “Multichannel CSMA with Signal Power-Based Channel Selection for Multihop Wireless Networks”, in Proc. of IEEE 52nd Vehicular Technology Conference, IEEE-VTS Fall VTC 2000.Vol. 1, Sept. 2000, Boston, MA,pp. 211-218, DOI10.1109/VETECF.2000.886655.

[23] Nitin Jain, Samir R. Das and AsisNasipuri(2001), “A Multichannel CSMA MAC Protocol with Receiver-Based Channel Selection for Multihop Wireless Networks”, in Proc. of Tenth International Conference on Computer Communications and Networks, Oct. 2001, Scottsdale, AZ, pp. 432-439, DOI 10.1109/ICCCN.2001.956301.

[24] Maria Papadopouli and PriyankPorwal(2006), “On-demand channel switching for multi-channel wireless MAC protocols”, in Proc. of 12th European Wireless Conference - Enabling Technologies for Wireless Multimedia Communications (European Wireless), Athens, Greece, Apr. 2006, pp. 1-12.

[25] L. Long and E. Hossain(2008), “OSA-MAC: A MAC Protocol for Opportunistic Spectrum Access in Cognitive Radio Networks”, in Proc. of IEEE Wireless Communications and Networking Conference, WCNC ‘08, Las Vegas, NV, Apr. 2008, pp. 1426-1430, DOI 10.1109/WCNC.2008.256.

[26] Shao-Yi Hung; Yu-Chun Cheng; Wu, E.H.-K.; Gen-Huey Chen(2008), “An Opportunistic Cognitive MAC Protocol for Coexistence with WLAN”, IEEE International Conference on Communications, ICC ’08, Beijing, China, May 2008, pp.4059-4063, DOI 10.1109/ICC.2008.762.

[27] Alex Chia-Chun Hsu, David S. L. Weiand C.-C. Jay Kuo(2007),“A Cognitive MAC Protocol Using Statistical Channel Allocation for Wireless Ad-hoc Networks”,in Proc. of IEEE Wireless Communications and Networking Conference, WCNC ’07, Kowloon,Mar. 2007, pp. 105-110, DOI 10.1109/WCNC.2007.25.

[28] Li-Chun Wang, Chung-Wei Wang, Yin-Chih Lu, and Chuan-Ming Liu (2007),“A Concurrent Transmission MAC Protocol for Enhancing Throughout and Avoiding Spectrum Sensing in Cognitive Radio”,in Proc. of IEEE Wireless Communications and Networking Conference, WCNC ’07, Kowloon, Mar. 2007, pp. 121-126, DOI 10.1109/WCNC.2007.28**.**

[29] Yogesh R Kondareddy and PrathimaAgrawal(2008), “Synchronized MAC Protocol For Multi-hop Cognitive Radio Networks”, in Proc. of IEEE International Conference onCommunications, ICC '08,Beijing, May 2008, pp. 3198-3202, DOI 10.1109/ICC.2008.602.

[30] WhaSookJeon, JeongAe Han and Dong GeunJeong(2012), “A Novel MAC Scheme for Multi-Channel Cognitive Radio Ad Hoc Networks”, IEEE Transactions on Mobile Computing, Vol. 11, No. 6,Jun. 2012, pp.1-30, DOI 10.1109/TMC.2011.118.

[31] Jianfeng Wang, Yuguang Fang and Dapeng Wu(2006), “A Power-Saving Multi-radio Multi-channel MAC Protocol for Wireless Local Area Networks”, in Proc. of 25th IEEE International Conference on Computer Communications, INFOCOM ’06, Barcelona, Spain,Apr. 2006,pp. 1-12, DOI 10.1109/INFOCOM.2006.277.

[32] TevfikYucek and HuseyinArslan(2009), “A Survey of Spectrum Sensing Algorithms for Cognitive Radio Applications”, IEEE Communications Surveys & Tutorials, vol. 11, no. 1, First Quarter 2009, pp. 116-130, DOI 10.1109/SURV.2009.090109.

[33] Byungjoo Lee, SeungHyong Rhee(2006),"Adaptive MAC Protocol for Throughput Enhancement in Cognitive Radio Networks", in Proc. of 25th IEEE International Conference on Computer Communications, INFOCOM '06, Busan, Jan, 2006, pp. 1-5, DOI 10.1109/ICOIN.2008.4472832.

[34] Shao-Yi Hung, Eric Hsiao-Kuang Wu, Gen-Huey Chen and Yu-Chun Cheng(2008), "An Opportunistic Cognitive MAC Protocol for Coexistence with WLAN", in Proc. of IEEE International Conference on Communications, ICC '08, Beijing, May 2008, pp. 4059-4063, DOI 10.1109/ICC.2008.762.

[35] Mohamed Elhawary and Zygmunt J. Haas(2008), "Busy Tone Multi Channel (BTMC): A New Multi Channel MAC protocol for Ad Hoc Networks", Sixth Annual IEEE International Conference on Pervasive Computing and Communications, Hong Kong, Mar. 2008, pp. 234-238, DOI 10.1109/PERCOM.2008.104.

[36] Hang Su and Xi Zhang(2008), "Channel-Hopping Based Single Transceiver MAC for Cognitive Radio Networks", in Proc. of 42nd Annual Conference on Information Sciences and Systems, CISS 2008, Princeton, NJ, Mar. 2008, pp. 197-202, DOI 10.1109/CISS.2008.4558520.

[37] Carlos Cordeiro and KiranChallapali(2007), "C-MAC : A Cognitive MAC Protocol for Multi-Channel Wireless Networks", in Proc. of 2nd IEEE International Symposium on New Frontiers in Dynamic Spectrum Access Networks, DySPAN'07,Dublin, Apr. 2007, pp. 147-157, DOI 10.1109/DYSPAN.2007.27.

[38] S M Kamruzzaman(2010),"CR-MAC: A Multichannel MAC Protocol for Cognitive Radio Ad Hoc Network", published in International Journal of Computer Networks and Communications(IJCNC) Vol. 2, No. 5 September 2010, DOI: 10.5121/ijcnc.2010.2501, 2010.

[39] Srinivasan Krishnamurthy, MansiThoppian, S. Venkatesan, and Ravi Prakash(2005),"Control Channel based MAC-Layer Configuration, Routing and Situation Awareness for Cognitive Radio Networks", in Proc. of Military Communications Conference, MILCOM '05, Atlantic City, NJ, Oct. 2005, Vol. 1, pp. 455-460, DOI10.1109/MILCOM.2005.1605725.

[40] Hao Nan, Tae-In Hyon and Sang-Jo Yoo(2007), “Distributed Coordinated Spectrum SharingMAC Protocol for Cognitive Radio”, in Proc. of 2nd IEEE International Symposium on New Frontiers in Dynamic Spectrum Access Networks, DySPAN’07,Dublin, Apr. 2007, pp. 240-249, DOI 10.1109/DYSPAN.2007.39.

[41] JunchengJia and Qian Zhang(2007), “Hardware-constrained Multi-Channel Cognitive MAC”, in Proc. of IEEE Global Telecommunications Conference, GLOBECOM '07, Washington, DC, Nov. 2007, pp. 4653-4658, DOI 10.1109/GLOCOM.2007.883.

[42] Kuo-Chun Huang and DipankarRoychaudhari(2011),”MAC Protocol Adaptation in Cognitive Radio Networks”,in Proc. of IEEE Wireless Communications and Networking Conference, WCNC ’11, Cancun, Quintana Roo, Mar. 2011, pp. 245-250, DOI 10.1109/WCNC.2011.5779135.

[43] TakChon Lou, Hsi-Lu Chao, Tzu-Jane Tsai(2009), “On synchronized channel sensing and accessing for cognitive radio users in IEEE 802.11 wireless networks”, in Proc. of IEEE 20th International Symposium on Personal, Indoor and Mobile Radio Communications, PIMRC ‘09, Tokyo, Japan, Sept.2009, pp.757-761, DOI 10.1109/PIMRC.2009.5450103.

[44] Shie-Yuan Wang, Yu-Ming Huang, Lee-Chin Lau, Chih-Che Lin(2011), “Enhanced MAC Protocol for Cognitive Radios over IEEE 802.11 Networks”, in Proc. of IEEE Wireless Communications and Networking Conference, WCNC ’11,Cancun, Quintana Roo, Mar. 2011, pp. 37-42, DOI 10.1109/WCNC.2011.5779103.

[45] The Network Simulator, Version ns-2.1b9a, http:/www.isi.edu/nsnam/ns/.

[46] The Network Simulator, Version ns-3.17, http://www.nsnam.org/